

LED gimbal

There are moments when you want the ability to direct light as you please. With our LED Gimbal recessed fixture, this has now become a reality with the easiest of installations.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
LEDDOWNG3	3"	8 W	600 lm	635 lm	90	3000 K	120 V
LEDDOWNG4	4"	8 W	600 lm	635 lm	90	3000 K	120 V
GMB4-3K	4"	11 W	810 lm	1000 lm	90	3000 K	120 V

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained
 Superior LED performance and lifespan
 30° tilting, 360° rotation
 Minimal heat emission
 Aluminum construction
 Low profile
 40° beam spread
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 Suitable for wet locations

Finish

BK Black
SN Satin Nickel
WH White

RFP-UNI


Universal rough-in plate

Order example


LEDDOWNG3-BK

3" gimbal recessed downlight with 600 Lumens at 3000 K in a black finish

LEDDOWNG3 Ø2 ¾" 




Ø3.375" x 2"




4.8125" x 2" x 2"

LEDDOWNG4 Ø2 ¾" 




Ø4.4375" x 2"




4.8125" x 2" x 2"

GMB4-3K Ø4 ¼" 



Ø4.8125" x 2.375"



5 3/8" x 3" x 1 1/4"